

Minimale Überströme / Maximale Vorsicherung

Abschaltung innert 5 Sekunden (Stromkreise ohne Steckdosen)															
Nennstrom	6	8	10	13	16	20	25	32	40	50	63	80	100	125	160
DIAZED	21	-	38	-	60	75	100	150	160	220	280	380	480	600	800
NH gL / gG	20	-	40	-	60	80	100	120	160	180	300	350	550	680	820
LS B / L	30	-	50	65	80	100	125	160	200	250	315	-	-	-	-
LS C / V	60	65	80	90	100	150	170	220	250	300	500	-	-	-	-
LS D / Z	-	-	100	100	110	150	170	220	250	300	500	-	-	-	-

Abschaltun innert 0.4 Sekunden (Steckdosenstromkreise)															
Nennstrom	6	8	10	13	16	20	25	32	40	50	63	80	100	125	160
DIAZED	34	-	55	-	80	120	160	240	280	350	510	680	900	-	-
NH gL / gG	30	-	60	-	100	140	200	270	300	310	510	640	960	680	820
LS B / L	30	-	50	65	80	100	125	160	200	250	315	-	-	-	-
LS C / V	60	65	100	130	160	200	250	320	400	500	630	-	-	-	-
LS D / Z	120	-	200	260	320	400	500	640	800	1'000	1'260	-	-	-	-